

Configuration variables for lcg-CE

IMPORTANT NOTE!!: Updated documentation for the configuration of lcg-CE is now under https://twiki.cern.ch/twiki/bin/view/LCG/Site-info_configuration_variables#lcg_CE.

These are all the necessary variables to configure the lcg CE.

- **site-info.def variables:**

- ◆ **Mandatory variables:** sys admins must define the following variables. They can be found in

```
opt/glite/yaim/examples/site-info.def:
```

```

◇ BATCH_SERVER
◇ BDII_HOST
◇ CE_BATCH_SYS
◇ CE_CPU_MODEL
◇ CE_CPU_SPEED
◇ CE_CPU_VENDOR
◇ CE_INBOUNDIP
◇ CE_LOGCPU
◇ CE_MINPHYSMEM
◇ CE_MINVIRTMEM
◇ CE_OS
◇ CE_SMP_SIZE
◇ CE_OS_RELEASE
◇ CE_OS_VERSION
◇ CE_OS_ARCH
◇ CE_OUTBOUNDIP
◇ CE_PHYSCPU
◇ CE_RUNTIMEENV
◇ CE_SF00
◇ CE_SI00
◇ GROUPS_CONF
◇ <queue-name>_GROUP_ENABLE
◇ JOB_MANAGER
◇ MON_HOST
◇ QUEUES
◇ SE_LIST
◇ USERS_CONF
◇ VOS
◇ VO_<vo-name>_VOMS_SERVERS
◇ VO_<vo-name>_SW_DIR
◇ VO_<vo-name>_VOMS_CA_DN
◇ VO_<vo-name>_VOMSES

```

This topic: LCG > Lcg-CE_configuration_variables

Topic revision: r7 - 2008-07-29 - MariaALANDESPRADILLO



Copyright &© 2008-2021 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

or Ideas, requests, problems regarding TWiki? use Discourse or Send feedback