

## How to make a "dev" version of Moore vxry in the pit

- make sure a corresponding Online varbdev exists (see online piquet guide<sup>?</sup>)
- logon to the online cluster
- ssh hlt\_oper@plus (ask Gerhard or Eric for the password)
- cd /group/hlt/MOORE/
- cp -R Moore\_vxry Moore\_vxrydev
- edit Moore\_vxrydev/cmt/project.cmt: Moore\_vxry -> Moore\_vxrydev and Online\_varb -> Online\_varbdev
- do the same with MooreSys/cmt/requirements, Hlt/Moore/cmt/requirements, and Hlt/Moore/cmt/version.cmt
- cd /group/hlt/MOORE/Moore\_vxrydev/MooreSys/cmt
- cmt br make
- cd Moore\_vxrydev/Moore/Hlt/Moore/job
- mv SetupMoore\_vxry.sh SetupMoore\_vxrydev.sh
- edit SetupMoore\_vxrydev.sh to use Moore\_vxrydev and Online\_varbdev
- edit runMoore\_EFF.sh, \${LHCBSERIALS}/SetupMoore\_vxry.sh -> /group/hlt/MOORE/Moore\_vxrydev/Hlt/Moore/job/SetupMoore\_vxrydev.sh
- test it with TDET or FEST

-- EricvanHerwijnen - 2009-10-01

---

This topic: LHCb > MooreDev

Topic revision: r2 - 2009-12-10 - EricvanHerwijnen



Copyright &© 2008-2020 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback