

# Table of Contents

<b>PandaDynamicDataPlacement.....</b>	<b>1</b>
<b>Introduction.....</b>	<b>2</b>
<b>General Policies.....</b>	<b>3</b>
<b>Tier 1 Algorithm.....</b>	<b>4</b>
<b>Tier 2 Algorithm.....</b>	<b>5</b>
<b>Logger.....</b>	<b>6</b>
<b>Monitor.....</b>	<b>7</b>
<b>Additional Information.....</b>	<b>8</b>

# PandaDynamicDataPlacement

# Introduction

This page describes PanDA Dynamic Data Placement (PD2P).

# General Policies

The following general policies apply to PD2P algorithm for making replicas of datasets at Tier 1 and Tier 2 sites.

- The dataset name prefix is `mc` or `data`
- The data type is not `RAW,RDO,HITS,ESD,EVNT`
- The `hidden` metadata is not `True`
- Destination of all PD2P datasets will be `DATADISK`
- Dataset replicas on `LOCALGROUPDISK` are ignored
- Skip `GangaRobot`, `HammerCloud`, `_dis`, `_sub` etc
- Site must have sufficient free space. The total disk size and disk usage are obtained using `DQ2.queryStorageUsage()`. The threshold is `max(totalDiskSize*5%,3TB)`.
- Site must be `analysis`, not `test`, `production` etc
- Replicas at non-online sites are ignored
- Only online sites are used

# Tier 1 Algorithm

It is specified as SELECTEDT1 in PD2P log.

- Primary copies of ATLAS data will be placed at Tier 1 sites based on CREM policies
- PD2P will make additional copy at Tier 1 if:
  - ◆ no PD2P replica was made during the past week to a T1
  - ◆  $\text{int}(\log_{10}(\text{nused})) > \text{nSecondaryT1Replicas}$ , where `nused` stands for how many times the dataset was used per jobset
  - ◆  $\log_{10}(\text{nused}) == 10^{*\text{int}(\log_{10}(\text{nused}))}$  (it means that another replica is created when `nused=10,100,1000,...` and not for `nused=1`)
- All T1s are used even if no T2 has `shcedconfig.cachedSE=True` in the cloud
- Location of additional 'secondary' copy is based strictly on MoU share
- If dataset is a container, each containing dataset is placed using MoU share
- immediately makes an additional copy at a Tier 2 using MoU share (SELECTEDT2\_T1MOU in PD2P log)

# Tier 2 Algorithm

Tier 2 Algorithm is executed independently of Tier 1 Algorithm. If one or more sites in a cloud have `shcedconfig.cachedSE=True`, the cloud is regarded as a PD2P cloud. When an analysis job is submitted to Panda, PD2P is triggered. Datasets which match the following conditions are distributed.

- The dataset was used one or more times before the job is submitted. I.e.,  $nUsed > 0$ , where  $nUsed$  is how many times the dataset was used beforehand
- No replica within PD2P T2 sites ( $nSitesHaveDS=0$ ). Or if  $nWaitingJobsets > 2$ , the number of replicas should be less than  $maxSitesHaveDS = \text{int}(\log_{10}(nWaitingJobs/200))$ .  $nWaitingJobsets$  is the number of Jobsets which have at least one waiting job.  $nWaitingJobs$  is the number of waiting jobs. Both  $nWaitingJobsets$  and  $nWaitingJobs$  are computed per dataset when the analysis job is submitted. The maximum value of  $maxSitesHaveDS$  is limited to 5. This condition is checked only for  $nUsed > 1$ , i.e., the second analysis job always triggers PD2P
- The number of active DQ2 subscriptions per dataset made by PD2P is not greater than 2

$maxSitesHaveDS$  is checked only for the second and subsequent analysis jobs. PD2P makes a copy at a candidate site with `shcedconfig.cachedSE=True` from any PD2P cloud by using the weight. The site must have fast FTS channel to sites which already have the replica. In PD2P log, it is specified as `SELECTEDT2_JOB` for  $nUsed=1$ , `SELECTEDT2_NOREP` for  $nSitesHaveDS=0$ , or `SELECTEDT2_WAIT` for others. Another copy is made at a Tier 2 using MoU share when  $nUsed=1$  (`SELECTEDT2_T2MOU` in PD2P log).

$$W_{T2} = \frac{W}{S \times R}$$

where

- $W$

... The same weight for analysis brokerage described in this link

- $S$  ... The number of subscriptions made by PD2P to the site for last 24 hours + 1
- $R$  ... The number of replicas of the dataset in T2 sites in the same cloud + 1

A new copy tends to go to another cloud due to the second negative weight if a T2 site in a cloud already has a copy. If the input is a dataset container, one candidate is found for each constituent dataset.

# Logger

PD2P Logger [↗](#)

- **action=UNSELECTEDT2** : Selection according to brokering algorithm
- **action=SELECTEDT2\_T2MOU** : Selection according to a/b/c/d classification

# Monitor

All the monitorings associated to PD2P and extracted from the logger informations are documented in PD2P Monitor



# Additional Information

- Slides, Tier 1 PD2P Plan [↗](#)
  - Slides, T1 PD2P Justification [↗](#)
  - Slides, Dataset age in PD2P [↗](#)
  - Slides, PD2P Dataset Tagging Proposal [↗](#)
  - Slides, T2 PD2P Experience [↗](#)
- 

## Major updates:

-- TadashiMaeno - 15-Nov-2010 -- Revised KaushikDe - 13-Apr-2011

**Responsible:** TadashiMaeno

**Never reviewed**

---

This topic: PanDA > PandaDynamicDataPlacement

Topic revision: r27 - 2013-02-21 - TadashiMaeno



Copyright &© 2008-2020 by the contributing authors. All material on this collaboration platform is the property of the contributing authors. Ideas, requests, problems regarding TWiki? Send feedback