

Table of Contents

Appendix C: TWiki CSS.....	1
Who should read this document?.....	1
Naming conventions.....	1
TWiki styles in core code.....	1
TWiki Styles in Plugins.....	2
TablePlugin.....	2
TWiki Styles in Templates.....	2
TWiki Styles used in configure.....	3
TWiki Styles in topics.....	3
TWiki Styles in Skins.....	3
Reserved Styles.....	4
Tips.....	4

Appendix C: TWiki CSS

Listing of CSS class names emitted from TWiki core code and standard plugins.

Who should read this document?

Most HTML elements generated by TWiki core code now have Cascading Style Sheet (CSS) tags. *Skin builders* and others who want to change the appearance of the default TWiki installation or any of the skins can use this document to see what styles can be created for these HTML elements.

Naming conventions

1. All TWiki class names have the prefix `twiki`. So: `twikiAlert`, `twikiToc`, etc. Remember that CSS class names are case sensitive - TWiki CSS uses lowercase `tw`.
2. If you define your own CSS classes, it is preferable that you do not use the `twiki` prefix to prevent undesired overriding effects.

A wide range of standard styles are used in the TWiki core code and topics, and more are used in plugins. The following is an exhaustive list of all styles defined by the PatternSkin. For the most part, the names are the only documentation of the purpose of the style. For more information on how these styles are used, read the code (sorry!)

TWiki styles in core code

<code>.twikiAlert</code>	<code>Client.pm, Form.pm, Statistics.pm</code>
<code>.twikiAnchorLink</code>	<code>Render.pm</code>
<code>.twikiCheckBox</code>	<code>Manage.pm</code>
<code>.twikiCurrentTopicLink</code>	<code>Render.pm</code>
<code>.twikiCurrentWebHomeLink</code>	<code>Render.pm</code>
<code>.twikiDiffAddedHeader</code>	<code>RDiff.pm</code>
<code>.twikiDiffAddedMarker</code>	<code>RDiff.pm</code>
<code>.twikiDiffAddedText</code>	<code>RDiff.pm</code>
<code>.twikiDiffChangedHeader</code>	<code>RDiff.pm</code>
<code>.twikiDiffChangedText</code>	<code>RDiff.pm</code>
<code>.twikiDiffDebug</code>	<code>RDiff.pm</code>
<code>.twikiDiffDebugLeft</code>	<code>RDiff.pm</code>
<code>.twikiDiffDebugRight</code>	<code>RDiff.pm</code>
<code>.twikiDiffDeletedHeader</code>	<code>RDiff.pm</code>
<code>.twikiDiffDeletedMarker</code>	<code>RDiff.pm</code>
<code>.twikiDiffDeletedText</code>	<code>RDiff.pm</code>
<code>.twikiDiffLineNumberHeader</code>	<code>RDiff.pm</code>
<code>.twikiDiffTable</code>	<code>RDiff.pm</code>
<code>.twikiDiffUnchangedText</code>	<code>RDiff.pm</code>
<code>.twikiDiffUnchangedTextContents</code>	<code>RDiff.pm</code>
<code>.twikiEditFormCheckboxButton</code>	<code>Form.pm</code>
<code>.twikiEditFormCheckboxField</code>	<code>Form.pm</code>
<code>.twikiEditFormDateField</code>	<code>Form.pm</code>
<code>.twikiEditFormError</code>	<code>Form.pm</code>
<code>.twikiEditFormLabelField</code>	<code>Form.pm</code>
<code>.twikiEditFormRadioField</code>	<code>Form.pm</code>

.twikiEditFormTextAreaField	Form.pm
.twikiEditFormTextField	Form.pm
.twikiEmulatedLink	Preview.pm
.twikiFirstCol	Render.pm
.twikiForm	Render.pm
.twikiGrayText	Manage.pm
.twikiHelp	Changes.pm
.twikiLink	Render.pm
.twikiNew	Changes.pm, Search.pm
.twikiNewLink	Render.pm
.twikiRadioButton	Form.pm
.twikiSummary	Manage.pm
.twikiToc	TWiki.pm
.twikiTocTitle	TWiki.pm
.twikiTopRow	Manage.pm
.twikiWebIndent	TWiki.pm

TWiki Styles in Plugins

TablePlugin

.twikiTable	The table
.twikiSortedCol	A sorted column
.twikiSortedAscendingCol	Sorted column, ascending
.twikiSortedDescendingCol	Sorted column, descending
.tableSortIcon	The sort icon holder (span)
.twikiFirstCol	The first column
.twikiTableEven	Even numbered rows
.twikiTableOdd	Odd numbered rows
.twikiTableCol + column number	Unique column identifier, for instance: .twikiTableCol0
.twikiTableRow + type + row number	Unique row identifier, for instance: .twikiTableRowdataBg0

TWiki Styles in Templates

.twikiPage	twiki.tmpl
.twikiMiddleContainer	twiki.tmpl
.twikiMain	twiki.tmpl
.twikiFormTable	formtables.tmpl, form.tmpl
.twikiFormTableHRow	formtables.tmpl, form.tmpl
.twikiFormTableRow	formtables.tmpl
.twikiFormTableFooter	formtables.tmpl
.twikiAttachments	attachtables.tmpl
.twikiEditForm	form.tmpl
.twikiSubmit	Submit button
.twikiSubmitDisabled	Disabled submit button
.twikiInputField	
.twikiInputFieldDisabled	
.twikiInputFieldReadOnly	
.twikiInputFieldFocus	For Internet Explorer that does not recognize the :focus pseudo class selector

TWikiCss < TWiki < TWiki

.twikiInputFieldBeforeFocus	for use with Javascript: the color of the input text when not clicked in the field
.twikiSelect	Select dropdown menu
.twikiTextarea	
.twikiTextareaRawView	
.twikiButton	
.twikiFocus	Behavior marker so a field can be given input focus
.twikiLeft	
.twikiRight	
.twikiClear	
.twikiHidden	
.twikiSmall	
.twikiBottomRow	
.twikiSRAuthor	
.twikiSRRev	
.twikiPageForm	
.twikiSeparator	
.twikiAccessKey	
.twikiLinkLabel	
.twikiFormSteps	container around a form, such as the attach form: attach.tmpl
.twikiFormStep	form row
.twikiNoBreak	no break on whitespace
.twikiMakeVisible	For elements that should only be visible with javascript on: default set to hidden, is made visible by javascript. Defaults to inline.
.twikiMakeVisibleInline	For span elements that should only be visible with javascript on: default set to hidden, is made visible by javascript.
.twikiMakeVisibleBlock	For div elements that should only be visible with javascript on: default set to hidden, is made visible by javascript.
.twikiMakeHidden	For elements that should be hidden with javascript on: no default style, is made hidden by javascript.
.twikiFooterNote	
.twikiPopUp	Behavior marker so a popup-window can be invoked
.twikiContentHeader	container around optional html placed before topic text
.twikiContentFooter	container around optional html placed after topic text

TWiki Styles used in configure

#twikiLogin	CSS.pm
.twikiFormSteps	CSS.pm
.twikiFormStep	CSS.pm

TWiki Styles in topics

.twikiBroadcastMessage	TWikiPreferences
#twikiSearchTable	WebSearch, WebSearchAdvanced

TWiki Styles in Skins

#twikiLogin	login.pattern.tmpl	
-------------	--------------------	--

Reserved Styles

.twikiImage	defined in PatternSkin	div creates border around enclosed image
.twikiNotification	defined in PatternSkin	temporary alert, lighter than broadcast message
.twikiUnvisited	defined in PatternSkin	link style that ignores the visited link state; useful for form links

Tips

PatternSkin makes extensive use of CSS in its templates. Read the PatternSkin topic and PatternSkinCss to learn more about creating your own CSS-based skin.

Practical introduction to CSS: <http://www.w3.org/Style/LieBos2e/enter/>

Related Topics: TWikiSkins, PatternSkin, DeveloperDocumentationCategory, AdminDocumentationCategory

This topic: TWiki > TWikiCss

Topic revision: r9 - 2010-06-24 - TWikiContributor



Copyright &© 2008-2021 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

or Ideas, requests, problems regarding TWiki? use Discourse or Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.TWikiCss