

EDITTABLE{ *attributes* } -- edit TWiki tables using edit fields and other input fields

- The %EDITTABLE{%} variable is handled by the EditTablePlugin
- Syntax: %EDITTABLE{ *attributes* }%

- Supported attributes:

Attribute	Comment	Default
header	Specify the header format of a new table like "	Food
format	The format of one column when editing the table. A cell can be a text input field, or any of these edit field types: ? Text input field (1 line): = =	text, <size>, <initial value>
changerows	Rows can be added and removed if "on" Rows can be added but not removed if "add" Rows cannot be added or removed if "off"	CHANGEROWS plugin setting
quietsave	Quiet Save button is shown if "on", hidden if "off"	QUIETSAVE plugin setting
include	Other topic defining the EDITTABLE parameters. The first %EDITTABLE% in the topic is used. This is useful if you have many topics with the same table format and you want to update the format in one place.	(none)
helptopic	Topic name containing help text shown below the table when editing a table. The %STARTINCLUDE% and %STOPINCLUDE% variables can be used in the topic to specify what is shown.	(no help text)
headerislabel	Table header cells are read-only (labels) if "on"; header cells can be edited if "off" or "0"	"on"
editbutton	Set edit button text, e.g. "Edit this table"; set button image with alt text, e.g. "Edit table, %PUBURL%/SYSTEMWEB%/TWikiDocGraphics/edittopic.gif"; hide edit button at the end of the table with "hide" (Note: Button is automatically hidden if an edit button is present in a cell)	EDITBUTTON plugin setting
buttonrow	Set to top to put the edit buttons above the table.	bottom
javascriptinterface	Use javascript to directly move and delete row without page refresh. Enable with "on", disable with "off".	JAVASCRIPTINTERFA plugin setting
redirectto	Set up a return page after saving changes. e.g By setting redirectto="%BASEPAGE%", you can return to base page if your editable table is included by another page.	(none)

- Example:

```
%EDITTABLE{ format="| text, 20 | select, 1, one, two, three |" changerows="on" }%
| *Name* | *Type* |
```

VarEDITTABLE < TWiki < TWiki

| Foo | two |

- Category: DatabaseAndFormsVariables, EditingAndContentUpdateVariables, TablesAndSpreadsheetsVariables
 - Related: See EditTablePlugin for more details
-

This topic: TWiki > VarEDITTABLE

Topic revision: r6 - 2019-07-03 - PeterJones



Copyright &© 2008-2020 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

or Ideas, requests, problems regarding TWiki? use Discourse or Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.VarEDITTABLE