

INCLUDE{"page"} -- include other topic or web page

- Merges the content of a specified page into the current one before rendering.
- **Syntax:** %INCLUDE{"page" ...}%
- Supported parameters:

Parameter:	Description:	Default:
"SomeTopic"	The name of a topic located in the current web, i.e. %INCLUDE{"WebNotify"}%	
"Web.Topic"	A topic in another web, i.e. %INCLUDE{"TWiki.SiteMap"}%	
"http://..."	A full qualified URL, i.e. %INCLUDE{"http://twiki.org:80/index.html"}%. Supported content types are text/html and text/plain. 💡 if the URL resolves to an attachment file on the server this will <i>automatically</i> translate to a server-side include.	
pattern="..."	Include a subset of a topic or a web page. Specify a RegularExpression that scans from start ('^') to end and contains the text you want to keep in parenthesis, e.g., pattern="^.*?(from here.*?to here).*". IncludeTopicsAndWebPages has more.	none
headingoffset="2"	Adjust the level of headings in the included topic. A "2" or "+2" increases the level by two, e.g. a ----+ H1 turns into a ----+++ H3. Positive and negative values are supported. Adjusted min and max levels are H1 and H6, respectively.	no adjustment
hidetoc="on"	Remove %TOC% in included content. Useful to show table of contents in individual topics, while suppressing them if included in a big master document.	TOC_HIDE_IF_INCLUDED setting
rev="2"	Include a previous topic revision; N/A for URLs	top revision
raw="on"	When a page is included, normally TWiki will process it, doing the following: 1) Alter relative links to point back to originating host, 2) Remove some basic HTML tags (html, head, body, script) and finally 3) Remove newlines from HTML tags spanning multiple lines. If you prefer to include <i>exactly</i> what is in the source of the originating page set this to on. raw="on" is short for disableremoveheaders="on", disableremovescript="on", disableremovebody="on", disablecompresstags="on" and disablerewriteurls="on".	disabled
literal="on"	While using the raw option will indeed include the raw content, the included content will still be processed and rendered like regular topic content. To disable parsing of the included content, set the literal option to "on".	disabled
disableremoveheaders="on"	Bypass stripping headers from included HTML (everything until first </head> tag)	disabled

VarINCLUDE < TWiki < TWiki

<code>disableremovescript="on"</code>	Bypass stripping all <code><script></code> tags from included HTML	disabled
<code>disableremovebody="on"</code>	Bypass stripping the <code></body></code> tag and everything around over and below it	disabled
<code>disablecompresstags="on"</code>	Bypass replacing newlines in HTML tags with spaces. This compression step rewrites unmatched <code><</code> 's into <code>&lt;</code> ; entities unless bypassed	disabled
<code>disablerewriteurls="on"</code>	Bypass rewriting relative URLs into absolute ones	disabled
<code>warn="off"</code>	Warn if topic include fails: Fail silently (if <code>off</code>); output default warning (if set to <code>on</code>); else, output specific text (use <code>\$topic</code> for topic name)	<code>%INCLUDEWARNING%</code> preferences setting
<code>section="name"</code>	Includes only the specified named section, as defined in the included topic by the <code>STARTSECTION</code> and <code>ENDSECTION</code> variables. Nothing is shown if the named section does not exist. <code>section=""</code> is equivalent to not specifying a section	
<code>PARAMONE="val 1"</code> <code>PARAMTWO="val 2"</code>	Any other parameter will be defined as a variable within the scope of the included topic. The example parameters on the left will result in <code>%PARAMONE%</code> and <code>%PARAMTWO%</code> being defined within the included topic. A default value for a variable can be specified in the included topic in case the corresponding parameter is not specified, such as <code>%PARAMONE{ default="..." }%</code>	

- Security Considerations:
 - ◆ The ability to `INCLUDE` arbitrary URLs, such as `%INCLUDE{"http://www.google.com/"}` is turned **off** by default. To turn this on, ask your TWiki administrator to enable the `{INCLUDE}{AllowURLs}` flag in the *Security setup* section of *configure*.
 - ◆ JavaScript in included web pages is filtered out as a security precaution per default. Disable filtering with `raw` or `disableremovescript` parameter.
- Examples: See `IncludeTopicsAndWebPages`
- Related: `BASETOPIC`, `BASEWEB`, `INCLUDINGTOPIC`, `INCLUDINGWEB`, `STARTINCLUDE`, `STOPINCLUDE`, `STARTSECTION`, `ENDSECTION`, `TOC`, `IncludeTopicsAndWebPages`, `ParameterizedVariables`

This topic: TWiki > VarINCLUDE

Topic revision: r8 - 2011-04-14 - TWikiContributor



Copyright &© 2008-2021 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

or Ideas, requests, problems regarding TWiki? use Discourse or Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.VarINCLUDE