

SETGETDUMP{...} -- dump variables

- Dump volatile or persistent name/values previously set with %SET{ }%. The %SETGETDUMP{ }%, %SET{ }%, and %GET{ }% variables are handled by the SetGetPlugin.
- Syntax: %SETGETDUMP{ remember="1" format="..." separator="..." }%
- Parameters:

Parameter	Description	Default
remember="1"	Dump all persistent variables	(volatile variables)
store="..."	Dump variables of a specific store	(volatile variables)
format="..."	Format output using variables \$name and \$value	"name: \$name, value: \$value "
separator="..."	String used for separating entries	"\n"

- Example: %SETGETDUMP{" | \$name | \$value |" separator="\$n"}% - see more examples.
- Category: ApplicationsAndComponentsVariables, DevelopmentVariables
- Related: GET, IF, SET, SetGetPlugin, SpreadSheetPlugin#FuncSET

This topic: TWiki > VarSETGETDUMP

Topic revision: r0 - 2015-04-09 - TWikiContributor



Copyright &© 2008-2021 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

or Ideas, requests, problems regarding TWiki? use Discourse or Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.VarSETGETDUMP