

GMTIME{"format"} -- formatted GM time

- Syntax: %GMTIME{"format"}%
- Supported variables:

Variable:	Unit:	Example
\$seconds	seconds	59
\$minutes	minutes	59
\$hours	hours	23
\$day	day of month	31
\$wday	day of the Week (Sun, Mon, Tue, Wed, Thu, Fri, Sat)	Thu
\$dow	day of the week (Sun = 0)	2
\$week	number of week in year (ISO 8601)	34
\$month	short name of month	Dec
\$mo	2 digit month	12
\$year	4 digit year	1999
\$ye	2 digit year	99
\$tz	either "GMT" (if set to gmtime), or offset such as "-0700" (if set to servertime)	GMT
\$iso	ISO format timestamp	2022-12-04T02:31:02Z
\$rcs	RCS format timestamp	2022/12/04 02:31:02
\$http	E-mail & http format timestamp	Sun, 04 Dec 2022 02:31:02 GMT
\$epoch	Number of seconds since 00:00 on 1st January, 1970	1670121062

- Variables can be shortened to 3 characters
- Example: %GMTIME{"\$day \$month, \$year - \$hour:\$min:\$sec"}% expands to 04 Dec, 2022 - 02:31:02
- **Note:** When used in a template topic, this variable will be expanded when the template is used to create a new topic. See TWikiTemplates#TemplateTopicsVars for details.
- Related: DISPLAYTIME, GMTIME, REVINFO, SERVERTIME

This topic: TWiki21Nov > VarGMTIME2

Topic revision: r4 - 2010-06-03 - TWikiContributor



Copyright &© 2008-2022 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

or Ideas, requests, problems regarding TWiki? use Discourse or Send feedback