

To be submitted to TIPP 2014 Amsterdam

For the session **Experiments: 2a) Experiments & Upgrades**

”Multi-component detector systems and upgrades to existing detectors. This subject includes special overview talks from the major experiments/projects across the fields (collider experiments, rare kaon/muon experiments, neutrino experiments, dark matter experiments, astrophysics experiments, large scale R&D projects etc). This conference and this track is not for polished talks about all that is beautiful and works well. We’d like to hear what the limitations are of the current experiments and how it limits the science and focus on ideas on how to break these barriers. The overview talks could reference/advertise the shorter (more focused) talks from the same experiment. Conveners: Massimiliano Ferro-Luzzi and Maria Chamizo”

The LHCb Upgrade Scintillating Fibre Tracker

Presenting Author^{1,2}

¹ Ruprecht-Karls-Universität, Heidelberg, 69120 DE

² on behalf of the LHCb SciFi Tracker collaboration

The Scintillating Fibre (SciFi) Tracker is designed to replace the current downstream tracking detectors in the LHCb Upgrade during 2018 [1]. The operation and the results obtained from the data collected 2011 and 2012 demonstrate that the current detector is robust and functioning very well. However, the limit of $\mathcal{O}(1 \text{ fb}^{-1})$ of data per year cannot be overcome without improving the detector. After 2018, it is planned to run with an increased luminosity of $1 - 2 \times 10^{33} \text{ cm}^{-2}\text{s}^{-1}$ to collect up to 50 fb^{-1} of data. This will be achieved using 25 ns bunch spacing with the average number of proton-proton interactions per bunch crossing $\nu = 3.8 - 7.6$. Collecting data at this luminosity will only be possible if the detector is improved by increasing the readout of the front-end electronics to 40MHz and implementing a more flexible software-based triggering system that will increase the data rate as well as the efficiency. The increase in interactions per bunch crossing will result in an increased occupancy in the tracking detectors and will exceed the operational occupancy for the Outer Tracker. Here we present the SciFi Tracker as the replacement for the Outer and Inner Trackers.

The SciFi Tracker is based on 2.5 m long multi-layered ribbons from 10,000 km of 0.250 mm diameter scintillating fibre as the active medium and signal transport over 12 planes covering 350 m^2 . Cooled silicon photomultiplier (SiPM) arrays with 128 channels and 0.25 mm channel width are used as readout. The front-end electronics are designed to digitize the signals from the SiPMS with a custom ASIC

chip, the PACIFIC, for the approximately 560,000 channels and reconstruct the track hit position within an on-board FPGA. Several challenges facing this detector will be presented regarding the precision construction of the large active detector components, the radiation hardness of the scintillating fibres and the SiPMs, the high density readout electronics, and the necessary cooling systems.

1. CERN/LHCC 2014-001; LHCb TDR 15